3 5 3 4 11. (Amended) [Electric motor unit] The motor unit of claim 1 wherein the motor unit is for a motorized fan group used in [the] at least one of a heater [and/or] and a fan [and/or] and an air conditioning unit of a motor vehicle[, characterized by being made up of a motor unit according to one of the preceding specifications].

REMARKS

After entry of this amendment, claims 1 - 11 have been amended.

A hand-written, corrected copy of the specification is enclosed showing the changes which have been made to the specification as required by Section 608.01(Q) and 714.20(1) of the Manual of Patent Examining Procedure. The Substitute Specification filed herewith has been amended to utilize idiomatic English, correct minor typographical and grammatical errors and to conform the application to current United States patent practice. The Substitute Specification includes no new subject matter; but does include the same changes handwritten in red in the attached, corrected, original specification. Entry of the Substitute Specification is respectfully requested.

It is submitted that this Amendment has antecedent basis in the application as originally filed, including the specification, claims and drawings, and that this Amendment does not add any new subject matter to the application. Consideration of the application as amended is requested.

Respectfully submitted,

YOUNG, BASILE, HANLON, MacFARLANE, WOOD & HELMHOLDT, P.C.

William M. Hanlon, Jr.

Attorney for Applicant(s) Registration No. 28422

(248) 649-3333

3001 West Big Beaver Rd., Suite 624 Troy, Michigan 48084-3107

Dated: September 7, 2000

WMH/dge

Electric motor unit, in particular, for a motor vehicle, incorporating an electronics for control of the unit electronic This invention involves an electric motor unit and an electronics for control of the motor. 3 4 The electric motor unit proposed by the invention can be advantageously used in a motorized fan used for the heater and/or vent and/or air conditioner of a motor vehicle. 5 6 Historically, the stator of such a motor unit is made up of a carbon carrying plate (PPC) which 7 presents, first, a brass insert and, second, a radiator. The brass insert serves to, first, guide the carbons and, second, to bring the current closer to the 8 MOSFET transistor lead from the power circuit to the right of the radiator. 9 10 The radiator, generally made of aluminum, recools the power components (diodes, MOSFET transistors) and presents casings into which certain electronic components carried by a circuit imprinted 11 12 with the command electronics are received and held. A motor unit of this type was described in the French patent application of the plaintiff disposed 13 13 under the number 98 03128. A goal of the invention is particularly, to propose a motor unit structure that allows very high tolerances of connections between the radiator and the brass insert. Another goal of the invention is to propose a motor unit structure, the rigidity and the watertightness of which is improved. also proposes [1] Still another goal of the invention is to propose a motor unit structure in which the means of connection and the assembly of the components are simplified The invention proposes an electric motor unit of a motor vehicle containing a wiper blade carrier plate that presents, first, a brass insert and second, a radiator, characterized by the plate presenting a 23 plastic over-molding that surrounds the insert and the radiator. 24 This over-molding allows it to make up for the play between the pieces. 25 In addition, it contributes to the rigidity of the plate, which allows optimization of the Conception of the radiator and the quantity of aluminum used for it, by removing from the radiator the 26 parts that are not necessary in its recooling and that only serve to increase the rigidity 27 28 Moreover, the over-molding also presents a partition that separates, in a waterproof way, on the

The area that is defined for the over-molding and which receives the card can, in addition, be

plate, the zone designed to receive the electronic card and a wiper blade.

closed by a lid for which the edge of the over-molding defines a watertight plane.

29

30

31

1

1	The combination of the over-moraning and the nais defined by the imprinted circuit card and the
2	electronic components (in the cold area of the motor) a watertight case in which they are thermically
3	isolated in relation to the zone that carries the brushes (electrotechnical zone - hot zone).
4	There is also an uncoupling between the electronic zone and the electrotechnical zone.
5	It can also, advantageously, be planned that on the separation partition the means of respiration
6	allowing circulation of the air from one zone to the other without allowing the entrance of moisture [in] 12
7	the electronic zone. BRIEF DESCIZIPTION OF THE DRAWING
8	Other characteristics and advantages of the invention will become more clear in the following
9	description. This description is purely illustrative and not limiting. It must be read in regards to the
10	attached drawings on which:
11	[- figure] Itis a cut view schematic representation of the motor unit conforming to one possible
12	method of production of the invention;
13	[- figure 2 is an exploded perspective view of a motor unit from figure 1;
₽ 4 m	[- figure 3 is a perspective schematic representation illustrating the connection of the plate to the
15	casing of the motor unit of figures 1 and 2; and
1114044018	- figure 4 is a detailed perspective representation of the mechanical means for the blockage of
F 7	the plate in relation to the casing DESCRIPTION OF THE PREFERED EMBODIMENT
	The motor unit which is illustrated in figures 1 and 2 contains a casing 1, a rotational axis 2, an
	inductor fixed in relation to the casing, and an inductor 4 powered by the brushes or carbons 5.
20 21	These brushes or carbons 5 are guided by a brass insert 6 which presents an electronic wiper
	blade carrier plate (PPCE) that also contains a radiator 7.
22	On this radiator 7 are placed power components (diodes, MOSFET transistors).
23	A printed circuit card C1, which carries control components, is also placed to the right of this
24	radiator 7.
25	The PPCE plate presents a over-molding 9 which surrounds the brass insert and the radiator.
26	This over-molding 9 also presents a partition 10 that separates, in a watertight manner, on the
27	plate, the zone that is designed to receive an electronic card C1, from the electrotechnical zone that
28	carries the brushes.
29	The peripheral over-molding and this partition 10 define, with a lid 12, a watertight case into
30	which is received the electronic card C1.
	electronics

	9
The peripheral	over-molding
which is received a	ioint 13 that is

1

2

3

4

7

8

9

10

11

12

马3 贞 可4

--15

16 017

□18

20 🚉

□ <u>□</u> 21

22

23

24

25

26

27

28

29

30

g and the transversal partition 10 together define a watertight plane is designed to be compressed between the lid 12 and the edge of the

histlid 12 is made up of a plastic hood 12a in which is placed a metallic-plated hood 12b.

This printed circuit card C1 is double-sided, the components reaching from one side of the card 5 to the other. 6

It is foreseen that the over-molding 9 casings allow the positioning and holding of the components before soldering them onto the card.

The power and control current is led to the electronic components (control components of the printed circuit card and power components (MOSFET, diodes) mounted on the radiator 7) by the stripe that presents the brass insert 6.

The brass insert is directly soldered to the printed circuit card or to the power components. removes, as a consequence, a connection level between the printed circuit card C1 and the brass insert. The links between the insert and the card C1 are thus optimized, which allows the considerable reduction of heating of the surface of the electronic card.

The power components like the MOSFET transistor and the diodes are cooled by the aluminum radiator 7, which is fitted with blades placed in the external air flux.

The radiator, the plastic over-molding, and the lid are assembled in such a manner to make up a watertight case vis-à-vis the exterior, but also from the interior of the motor (thermal protection, protection from dust, protection from electromagnetic rays, etc.)

The means allowing the removal of condensation produced by the radiator 7 in the case defined by the over-molding 9 and the lid 12 are advantageously foreseen for in the watertight partition 10. Also, the over-molding 9 presents the means for the passage of the wires designed to power the brass insert (cut 17). Particularly, the over-molding contains means allowing the implantation of a connecting module designed to power the insert and the electronic controls and allows the connection towards the exterior by a complimentary connector.

The electrotechnical part is closed by a flask F.

As one can see in figures 2 to 4, the over-molding 9 of the plate presents elastic attachment flaps 14 designed to work with complimentary forms 15 can come from the stamping that presents the case 1, in order to stabilize the plate in relation to the case 1.

,	+ upically
1	One will note that one solution for attachment is particularly economical; habitually, the means
2	of attaching the plate on the case are made up of rolled-stapled sheet metal.
3	The elastic leads 14 and the complimentary forms 15 that present the case are, for example,
4	restarted in such a way to create a limitation imposing a single possible position relative between the
5	plate and the case.
6	For example, the leads 14 and the forms 15 are angularly spaced respectively two by two at
7	115°, 115°, 130°. Figure
8	As is illustrated on figure 4, the elastic leads 14 end, for example, by beveled protuberances 16
9	that facilitate the connection of the plate onto the case and assure, during of the connection, the
10	mechanical stabilization of the ensemble by avoiding the lowering of the plate under the counterweight
11	of the electronics incorporated into the motor.